

## Safewash 2000

**Product Code: SWA400H**

### PRODUCT DESCRIPTION

An aerosol containing a unique blend of biodegradable solvents in an aqueous medium formulated to replace CFCs or highly flammable cleaning solvents in electronic applications. A full range of bulk **Safewash** is also available for use in ultrasonic and pressure spray applications.

### PRODUCT USE

Excellent flux removal properties ensure fast and effective cleaning of printed circuit boards, electronic assemblies and print screens. The unique foaming action dissolves and lifts dirt/ flux from the surface. The foam ensures good contact time, hence economical use of the product.

### FEATURES

- \* 100% Ozone Friendly
- \* Biodegradable
- \* Fast, effective foam action
- \* Low corrosivity
- \* Cleans to MIL P 28809A

### TYPICAL PROPERTIES

Boiling Point	100°C
Flash Point	None

### DIRECTIONS FOR USE


Spray aerosol onto area to be cleaned. Leave foam on assembly for 2 to 3 minutes. Brushing may be required to remove stubborn deposits. Rinse thoroughly with tapwater and then rinse off with **Saferinse 2000** which removes the last trace of ions and aids drying. Dry with warm air, or with **Electrolube Airduster**. Test before use on sensitive materials eg. ABS, Acrylic, Polycarbonate, Polystyrene.

### TECHNICAL DATA SHEET



### Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## Safewash 2000 – Page 2

### PACKAGING

400 ml Aerosol with integral brush

### ORDER CODE

SWA400H

### TECHNICAL DATA SHEET



### Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

